

L & M SUPPLY CO., INC.

P.O. Box 640
1800 Springhead Ch. Rd.
Willacoochee, Ga. 31650

912-534-6071
800-948-7870
912-534-6254(fax)

To whom it may concern:

Subject: **Certification of LMSF-A100 Silt Fence**

This letter certifies that our silt fence fabric meets and/or exceeds the specifications listed below. The average laboratory test values for the LMSF-A100 silt fence are as follows:

| PROPERTY | TEST METHOD | UNIT | ROLL VALUE |
|-----------------|-------------|-----------|--------------|
| Grab Tensile | ASTM D 4632 | Lbs | 125 |
| Grab Elongation | ASTM D 4632 | % | 20 |
| Trap Tear | ASTM D 4533 | Lbs | 65 |
| Mullen Burst | ASTM D 3786 | Psi | 275 |
| Puncture | ASTM D 4833 | Lbs | 70 |
| AOS | ASTM D 4751 | Sieve(mm) | 30 |
| Flow Rate | ASTM D 4491 | Gpm/ft | 90 |
| UV Resistance | ASTM D 4355 | %hours | 80% @ 500hrs |

Unless otherwise noted, this certification is based on testing conducted by an independent testing laboratory. These test results are no more than one year old when presented to the authorizing agent. L & M Supply Co., Inc. issued this letter of certification to indicate our commitment to providing our customers with a quality product which will meet or exceed the minimum average roll values in accordance with the applicable American Society for Testing and Materials (ASTM) test method.

Respectfully,

Quincy McMillan
L&M Supply Co., Inc.